

THE WHITCO

AQUEOUS PARTS WASHER

There's still no substitute for quality.



Solvent-Free!

**Biodegradable
detergents &
hot water!**

Whitco
CLEANING SYSTEMS

SPECIFICATIONS

| MODEL | ← TOP LOAD → | | | ← FRONT LOAD → | | | | |
|----------------------|----------------|----------------|----------------|----------------|----------------|-----------------|----------------|-----------------|
| | W10 | W12 | W13 | W12-4 | W12-6 | W12A-8 | W12B-8 | W12C-8 |
| OVERALL HEIGHT | 52" | 65" | 65" | 78" | 84" | 102" | 108" | 108" |
| OVERALL WIDTH | 40" | 52" | 52" | 60" | 72" | 76" | 80" | 88" |
| OVERALL DEPTH | 34" | 46" | 46" | 41" | 52" | 66" | 60" | 70" |
| TURNTABLE DIAMETER | 24" | 26" | 26" | 26" | 36" | 36" | 40" | 48" |
| WORKING HEIGHT | 18" (28"Opt) | 32" (*) | 32" (*) | 40" (*) | 42" (*) | 54" (*) | 60" (*) | 60" (*) |
| TURNTABLE LOAD LIMIT | 300 lbs. | 500 lbs. | 500 lbs. | 800 lbs. | 1000 lbs. | 1000 lbs. | 2000 lbs. | 2000 lbs. |
| SOLUTION CAPACITY | 25 gals | 50 gals | 70 gals | 70 gals | 120 gals | 225 gals | 240 gals | 250 gals |
| NOZZLE ORIFICE | 3/16" | 3/16" | 3/16" | 3/16" | 3/16" | 3/16" | 3/16" | 3/16" |
| PUMP MOTOR | 2 HP | 3 HP | 3 HP | 5 HP | 7 1/2 HP | 15 HP | 15 HP | 15 HP |
| TURNTABLE MOTOR | N/A | 1/15 HP | 1/15 HP | 1/15 HP | 1/15 HP | 1/2 HP | 1/2 HP | 1/2 HP |
| PUMP CAPACITY | 36 gpm @40 psi | 50 gpm @45 psi | 50 gpm @45 psi | 90 gpm @60 psi | 100 gpm @60psi | 190 gpm @65 psi | 200 gpm @65psi | 210 gpm @65 psi |
| ELECTRIC WASH HEATER | 4.5 KW | 6 KW | 6 KW | 12 KW | 12 KW | 18 KW | 18 KW | 18 KW |
| APPROXIMATE WEIGHT | 530 lbs | 1000 lbs | 1250 lbs | 1500 lbs | 1850 lbs | 3500 lbs | 4500 lbs | 5500 lbs |
| OPTIONS | W10 | W12 | W13 | W12-4 | W12-6 | W12A-8 | W12B-8 | W12C-8 |
| 7 DAY HEAT TIMER | Opt | Opt | Opt | Opt | Opt | Std | Std | Std |
| 7 DAY SKIM TIMER | Opt | Opt | Opt | Opt | Opt | Opt | Opt | Opt |
| OIL SKIMMER | Opt | Opt | Opt | Opt | Opt | Opt | Opt | Opt |
| EVAPORATION CYCLE | Opt | Opt | Opt | Opt | Opt | N/A | N/A | N/A |
| RINSE WITH DIVERTER | N/A | N/A | N/A | Opt | Opt | Std | Std | Std |
| PARTS BASKET | N/A | Std | Std | Std | Std | Std | Std | Std |
| AUTO FILL | Opt | Opt | Opt | Opt | Opt | Opt | Opt | Opt |
| LOW WATER SHUT-OFF | Std | Opt | Opt | Opt | Opt | Opt | Opt | Opt |
| THERMOMETER | Opt | Opt | Opt | Opt | Opt | Std | Std | Std |
| S.S. NOZZLES | Opt | Opt | Opt | Opt | Opt | Std | Std | Std |
| LOWER SPRAY BAR | Opt (28") | Opt | Opt | Opt | Opt | Opt | Opt | Opt |
| DUAL T.T. | N/A | Opt | Opt | Opt | Opt | Opt | Opt | Opt |
| BAG FILTER | 4" Opt | 6" Opt | 6" Opt | 6" Opt | 8" Opt | 8" Opt | 8" Opt | 8" Opt |
| OPTIONAL PUMPS | 3 HP | 5 HP | 5 HP | 7.5 HP | 15 HP | 20 HP | 20 HP | 20 HP |
| GAS HEAT | N/A | Opt | Opt | Opt | Opt | Opt | Opt | Opt |
| OIL HEAT | N/A | Opt | Opt | Opt | Opt | Opt | Opt | Opt |
| STEAM HEAT | N/A | Opt | Opt | Opt | Opt | Opt | Opt | Opt |
| CASTERS | Opt | Opt | Opt | N/A | N/A | N/A | N/A | N/A |
| HEAD RACK | N/A | Opt | Opt | Opt | Opt | Opt | Opt | Opt |
| INSULATION | N/A | N/A | Std | Std | Std | Std | Std | Std |
| 230 V, 1 0 POWER | Std | Std | Std | Opt | Opt | N/A | N/A | N/A |
| 230 V, 3 0 POWER | Opt | Opt | Opt | Std | Std | Std | Std | Std |
| SPECIAL VOLTAGE | Opt | Opt | Opt | Opt | Opt | Opt | Opt | Opt |
| TRANSMISSION BAR | N/A | Opt | Opt | Opt | Opt | Opt | Opt | Opt |

* 40"/48" Opt. Other sizes available upon request. ** Belt type optional
SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.